

HomeAdvantage Series

Premium residential models



Features

- ▶ External fingertip digital temperature control
- ▶ LED temperature display
- ▶ Self modulating heating elements
- ▶ $\frac{3}{4}$ " quick connect water connections
- ▶ Available in 1, 2, 3 or 4 modules
- ▶ Adjustable temperature range from 100 °F to 140 °F via digital control pad

Benefits

- ▶ Sleek stainless steel exterior

The Specs

MODEL	VOLTS	kW	AMPS	RECOMMENDED WIRE SIZE (CU)	MIN. FLOW	MAX. GPM	APPRX. WEIGHT	TEMPERATURE RISE °F							
								1.0 GPM	1.5 GPM	2.0 GPM	2.5 GPM	3.0 GPM	4.0 GPM	5.0 GPM	6.0 GPM
1 MODULE															
SS012240T	240V*	11.5kW	48A	6AWG	0.7 GPM	2.5 GPM	4.5 lbs.	77°	52°	39°	31°	-	-	-	-
2 MODULES															
SS015240TC	240V*	15kW	64 (2x32)A	8AWG	0.7 GPM	3.0 GPM	10.5 lbs.	-	68°	51°	41°	34°	-	-	-
SS019240TC	240V*	19kW	80 (2x40)A	8AWG	0.7 GPM	3.0 GPM	10.5 lbs.	-	87°	65°	52°	43°	-	-	-
SS023240TC	240V*	23kW	96 (2x48)A	6AWG	0.7 GPM	3.5 GPM	10.5 lbs.	-	105°	79°	62°	54°	-	-	-
3 MODULES															
SS029240T2T	240V*	28.5kW	120 (3x40)A	8AWG	0.7 GPM	4.0 GPM	15 lbs.	-	-	-	76°	65°	49°	-	-
4 MODULES															
SS038240T2T2	240V*	38kW	160 (4x40)A	8AWG	0.9 GPM	6.0 GPM	20 lbs.	-	-	-	103°	86°	65°	52°	43°

*240V units can be used on 208V with 25% reduced temperature output

Applications

- ▶ Single sink
 - ▶ Whole bathroom
 - ▶ Whole house
 - ▶ Up to 3 showers and 3 sinks for the largest unit
 - ▶ Good for addition construction where hot water is needed
- 